


Product Status	<a href="#">Production</a>
Sales Region	Worldwide
Series	RWS-B/DIN
Model	RWS150B/DIN
Feature	Complies with SEMI F47
Options	DIN rail mountable
Option Lineup	<a href="#">Please refer to here.</a>
Recommended EMC Filter	<a href="#">Please refer to here.</a>
Accessories	<a href="#">Please refer to here.</a>
Brand	TDK-Lambda
Environmental Compliance	



Electrical Characteristics	
Input	Single-phase
Input Voltage Range[AC]	85 to 265Vac
Input Voltage Range[DC]	120 to 370Vdc
Efficiency	89% Typ.
Rated Output Voltage[DC]	24Vdc
Output Voltage Range[DC]	21.6 to 27.6Vdc
Maximum Output Current	6.5A
Maximum Output Power	156W

Package Type & Size	
Package / Mounting	DIN rail
Industry Standard Size	
Width(W)	43mm Nom. (1.69in Nom.)
Height(H)	134.7mm Nom. (5.30in Nom.)
Depth(D)	139.9mm Nom. (5.51in Nom.)
Weight	770g Typ. (1.7lbs Typ.)

Other	
Operating Temp. Range	-20 to 70°C
Cooling	Convection

! Images are for reference only and show exemplary products.  
! This PDF document was created based on the data listed on the TDK Corporation website.  
! All specifications are subject to change without notice.

Safety Standard(Certified)	CSA60950-1
	EN60950-1
	UL60950-1
	CSA62368-1
	EN62368-1
	UL62368-1
	CSA C22.2 No.107.1-01
	UL508
Safety Standard(Conformed)	Den-an Appendix 8 at 100VAC only
Remarks	This page only shows representative characteristics. Please refer to the technical data for detailed specifications and conditions.